



Model

GS108

8-Port Gigabit
Desktop Switch



[Datasheet](#)



Features

- 8*Gigabit RJ45 Ports
- Apply to IEEE802.3、IEEE802.3u、IEEE802.3ab standard
- Ethernet ports support 10/100/1000M adaptive
- Support Auto MDI/MDIX
- Panel indicators to monitor working status and help fault analysis
- Flow control, full duplex adopts IEEE802.3x standard, half duplex adopts Backpressure standard
- Port 1-2 supports Qos data priority



Specifications

Product Model	GS108	
Standards Protocol	IEEE 802.3, IEEE 802.3u, IEEE802.3ab, IEEE802.3x	
Interface	8 x 10/100/1000Mbps Auto-Negotiation ports	
Network Media	10Base-T : Cat3,4,5 or above UTP(≤100m)	
	100Base-TX : Cat5 or above UTP(≤100m)	
	1000Base-TX : Cat5 or aboveUTP(≤100m)	
Transfer Method	Store-and-Forward	
MAC Address Table	8K	
Switching Capacity	16 Gbps	
Packet Forwarding Rate	11.9 Mbps	
Packet Buffer	4 Mbit	
Jumbo Frame	15K Byte	
LED Indicators	PWR	On: power on
		Off: no power
	Link	On: 10/100/1000M link connection is normal
		Blinking: Data transmission is normal Off: link failure
Product Size	138*78*25mm	
Input Voltage	DC 5V0.55A	
Environment	Operating Temperature: -10°C~50°C	
	Storage Temperature: -40°C~70°C	
	Operating Humidity: 10%~90% non-condensing	
	Storage humidity: 5%~95% non-condensing	