



NOTE:

1. ELECTRICAL TEST:100% OPEN SHORT, MISS WIRE TEST
2. FLUKE Channel TEST:
TEST LIMIT:ISO11801 Channel Class EA
3. Working temperature:-10°C~+60°C
Storage temperature:-20°C~+75°C
4. RoHS2.0 AND REACH compliant
5. Spray WORD:CAT6A U/FTP 4x2x32AWG/7 Ultraflex LSZH-TPE ISO11801 & EN50173 & ANSI/TIA568C.2
6. Minimum of the bending radius is 15mm(Suitable for all meters)

PIN OUT



CN1 (568B) CN2 (568B)



MATERIAL LIST

③	OVER MOLD	75A PVC GREY(RAL7035)	2	
②	PLUG	RJ45 8P8C Shielded Plug, PIN GOLD PLATED 3u", THE SHELL PLATED NICKEL, COLOUR:TRANSPARENT	2	
①	CABLE	CAT. 6A U/FTP CABLE (32AWG BC*1P+AL-FOIL)*4+DRAIN JACKET:ULTRAFLEX LSZH-TPE/GREY (RAL7035), OD:3.6±0.2MM	1	
NO.	PARTS NAME	SPECIFICATION STANDARD	QT' Y	REMARK

Item NO.	Length (mm)
21.44.3300	150±10
21.44.3301	300±10
21.44.3302	500±20
21.44.3303	1000±20
21.44.3304	1500±30
21.44.3305	2000±30
21.44.3306	3000±50
21.44.3307	5000±100

DESC.	ROLINE GREEN Cat.6A U/FTP Patch cord 10G Slim Type Ultraflex LSZH-TPE, grey
-------	---

		NEW	2022-07-01	A
BY	CHK	REVISION RECORD MODIFICATIONS	DATE	REV.

