


WIRING DIAGRAM



NOTE:

- ELECTRICAL TEST:100% OPEN SHORT, MISS WIRE TEST
- FLUKE Channel LINK TEST:
TEST LIMIT:ISO11801 Channel Class EA
- Working temperature:-20°C~+75°C
Storage temperature:-20°C~+80°C
- RoHS AND REACH compliant
- Spray WORD:CAT6A S/FTP with 600MHz cat.7 raw cable
4x2x26AWG/7 RECYCLED TPE ISO11801 & EN50173 & ANSI/TIA568.2-D
- Minimum of the bending radius is 4*OD (Suitable for all meters)

MATERIAL LIST:

| | | | | |
|-----|------------|---|------------|--------|
| ③ | OVER MOLD | RECYCLED PVC RED PANTONE 199C | 2 | |
| ② | PLUG | RJ45 8P8C SHIELDED PLUG PIN GOLD PLATED 3U", THE SHELL PLATED NICKEL, COLOUR: TRANSPARENT GREEN | 2 | |
| ① | CABLE | S/FTP CAT. 7 26AWG (BC+RECYCLED INSULATION+AL-FOIL)*4P+ BRAID (AL-MG) JACKET: RECYCLED TPE RED PANTONE 199C OD: 6.0±0.2MM | 1 | |
| NO. | PARTS NAME | SPECIFICATION DESCRIPTION | QT'Y | REMARK |
| | | NEW | 2023-11-30 | A |
| BY | CHK | REVISION RECORD MODIFICATIONS | DATE | REV. |

| | | | |
|------------|---|-------------|--|
| 21.45.3219 | ROLINE RECYCLED S/FTP PatchCord Cat6A/C1.EA, TPE, red, 20m | 20000±300 | 53.40% |
| 21.45.3218 | ROLINE RECYCLED S/FTP PatchCord Cat6A/C1.EA, TPE, red, 15m | 15000±300 | 53.40% |
| 21.45.3217 | ROLINE RECYCLED S/FTP PatchCord Cat6A/C1.EA, TPE, red, 10m | 10000±300 | 53.40% |
| 21.45.3216 | ROLINE RECYCLED S/FTP PatchCord Cat6A/C1.EA, TPE, red, 7m | 7000±150 | 53.30% |
| 21.45.3215 | ROLINE RECYCLED S/FTP PatchCord Cat6A/C1.EA, TPE, red, 5m | 5000±100 | 53.30% |
| 21.45.3213 | ROLINE RECYCLED S/FTP PatchCord Cat6A/C1.EA, TPE, red, 3m | 3000±50 | 53.10% |
| 21.45.3212 | ROLINE RECYCLED S/FTP PatchCord Cat6A/C1.EA, TPE, red, 2m | 2000±30 | 53.00% |
| 21.45.3214 | ROLINE RECYCLED S/FTP PatchCord Cat6A/C1.EA, TPE, red, 1.5m | 1500±30 | 52.90% |
| 21.45.3211 | ROLINE RECYCLED S/FTP PatchCord Cat6A/C1.EA, TPE, red, 1m | 1000±20 | 52.60% |
| 21.45.3210 | ROLINE RECYCLED S/FTP PatchCord Cat6A/C1.EA, TPE, red, 0.5m | 500±20 | 52.10% |
| 21.45.3271 | ROLINE RECYCLED S/FTP PatchCord Cat6A/C1.EA, TPE, red, 0.3m | 300±10 | 51.70% |
| ITEM NO. | DESC. | LENGTH (mm) | The proportion of RECYCLED certification materials |

