



10130-198 VARISTAR MIL CABINET, EMC SHIELDED, MIL 901D, WITH CABLE SHOCK ABSORBERS



KEY FEATURES

Cabinet IP-55 for extreme seismic and mobile conditions (with shock absorbers)

Tested to MIL-STD-901D

Doubly protected against corrosion, zinc-plated and powder-coated

4 shock absorbers at bottom and 2 shock absorbers at top

EMC protection 60 dB at 1 GHz, 40 dB at 3 GHz (IEC 61587-3)

Rear panel horizontally partitioned for fitting of e.g. cable ducting

PRODUCT ATTRIBUTES

Product Type: Cabinet

Product Family: Varistar

Frame Material: Steel

Frame Color: Pebble Grey

Frame Color Code: RAL 7032

Cladding Material: Steel

Cladding Color: Pebble Grey

Cladding Color Code: RAL 7032

Rack Height: 38 U

Height: 1800 mm

Width: 600 mm

Depth: 800 mm

Static Load: 1600 kg

Dynamic Load: 150 kg

Protection Rating: IP55

Complies With: IEC 60529; IEC 61587-1; IEC 60297-3-100; IEC 61587-3; IEC 61587-1; MIL-S-901D

ADDITIONAL PRODUCT DETAILS

Cabinet with MIL901D, IP 55 and EMC compliance for extreme seismic and mobile conditions with shock absorbers. The enclosures are for frigate, airforce and military applications.

Other dimensions and versions on request.

CERTIFICATIONS



North America

All locations

+1.763.422.2661

Chat with us:

schroff.nvent.com

Europe

Straubenhardt, Germany

+49.7082.794.0

Betschdorf, France

+33.3.88.90.64.90

Warsaw, Poland

+48.22.209.98.35

Assago, Italy

+39.02.932.7141

Chat with us:

schroff.nvent.com

Asia

Shanghai, China

+86.21.2412.6943

Qingdao, China

+86.532.8771.6101

Singapore

+65.6768.5800

Shin-Yokohama, Japan

+81.45.476.0271

Chat with us:

schroff.nvent.com

Middle East & India

Dubai, United Arab Emirates

+971.4.378.1700

Bangalore, India

+91.80.6715.2001

Istanbul, Turkey

+90.216.250.7374

Chat with us:

schroff.nvent.com



Our powerful portfolio of brands:
nVent.com **CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER**

© 2023 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.

nVent reserves the right to change specifications without notice.