19-inch server cabinet Basic "perforated door"



Data sheet





The server cabinets in the ROLINE Basic series have been developed to enable simple and particularly cost-efficient network expansion. Strategically placed cable inlets ensure effortless installation depending on the application. Each cabinet consists of a robust steel construction with a material thickness of up to 1.5 mm sheet steel.

Characteristics:

- Load capacity: 600 or 1000 kg
- Front & rear doors made of 70% perforated steel
- Locking system with swivel lever handle on front and rear doors
- 1-point locking system on all doors
- Side panels are lockable and removable
- Double-leaf rear door
- Floor with punched cable inlet
- Roof with cut-out for fan modules
- Pre-assembled 4 levelling feet
- Incl. fixing material
- Colour: Light grey, RAL 7035 or Jet black, RAL 9005
- IP protection class: IP20
- Mounted: Yes

19-inch server cabinet Basic "perforated door"



Data sheet

The ROLINE Basic series offers a versatile selection of network and server enclosures in various height units from 26 U to 42 U and in the colours grey (RAL 7035) and black (RAL 9005).

Manuf. no.	Height	Width (mm)	Depth (mm)	Colour / RAL
26.21.0034	26 U	600	1000	grey / RAL 7035
26.21.0203	26 U	600	1000	black / RAL 9005
26.21.0041	42 U	600	1000	grey / RAL 7035
26.21.0210	42 U	600	1000	black / RAL 9005
26.21.0045	42 U	800	1000	grey / RAL 7035
26.21.0214	42 U	800	1000	black / RAL 9005
26.21.0046	42 U	800	1000	grey / RAL 7035
26.21.0215	42 U	800	1000	black / RAL 9005

Manuf. no.	Incl. cable routing channels	Maximum weight capacity (kg)
26.21.0034	No	600
26.21.0203	No	600
26.21.0041	No	1000
26.21.0210	No	1000
26.21.0045	Yes	1000
26.21.0214	Yes	1000
26.21.0046	No	1000
26.21.0215	No	1000

19-inch server cabinet Basic "perforated door"



Data sheet



Front door made of 70% perforated steel



Removable side panels



Base plate with cable feed



1-point locking on all doors



Locking system with swivel lever handle



Roof with cut-outs for ventilation