



APC Smart-UPS Ultra On-Line SRTL2KRM1UIC, 2kW, 1U Rack/Tower/Wand, , 3x C13 & 2x C19, SmartConnect

Marke : APC

Artikel-Code: SRTL2K2RM1UIC

Produktname : APC Smart-UPS Ultra On-Line SRTL2KRM1UIC, 2kW, 1U Rack/Tower/Wand, , 3x C13 & 2x C19, SmartConnect



APC Smart-UPS Ultra On-Line SRTL2KRM1UIC, 2kW, 1U Rack/Tower/Wand, , 3x C13 & 2x C19, SmartConnect

APC Smart-UPS Ultra On-Line SRTL2KRM1UIC, 2kW, 1U Rack/Tower/Wand, , 3x C13 & 2x C19, SmartConnect. USV-Topologie: Doppelwandler (Online), Ausgangskapazität: 2,2 kVA, Ausgangsleistung: 2200 W. AC-Steckertypen: C13-Koppler, C19-Koppler, Stecker: Typ F, Anzahl der AC-Ausgänge: 5 AC-Ausgänge. Akku-/Batterietechnologie: Lithium-Ion (Li-Ion), Akku-/Batteriespannung: 50 V, Akkuladezeit: 1,5 h. Formfaktor: Rackmount, Produktfarbe: Schwarz, Silber, Rack-Kapazität: 1U. Breite: 432 mm, Tiefe: 560 mm, Höhe: 43 mm



Merkmale		Design	
USV-Topologie *	Doppelwandler (Online)	Steuerung	Berührung
Ausgangskapazität *	2,2 kVA	Display-Typ	LCD
Ausgangsleistung *	2200 W	LED-Anzeigen	✓
Wellenform *	Sine	Internationale Schutzart (IP-Code)	IP20
Eingangs-Betriebsspannung (min) *	160 V	Zertifizierung	EN/IEC 62040-1
Eingangs-Betriebsspannung (max) *	275 V	Betriebsbedingungen	
Eingangsfrequenz *	50/60 Hz	Betriebstemperatur	0 - 40 °C
Notstrom Aus (EPO)	✓	Temperaturbereich bei Lagerung	-15 - 45 °C
Geräuschpegel	55 dB	Relative Luftfeuchtigkeit in Betrieb	0 - 95%
Anschlüsse und Schnittstellen		Luftfeuchtigkeit bei Lagerung	0 - 95%
AC-Steckertypen	C13-Koppler, C19-Koppler	Höhe bei Betrieb	0 - 3048 m
Stecker	Typ F	Höhe bei Lagerung	0 - 15240 m
Anzahl der AC-Ausgänge	5 AC-Ausgänge	Technische Details	
Serielle Schnittstelle	✓	Nachhaltigkeitskonformität	✓
Anzahl Ethernet-LAN-Anschlüsse (RJ-45)	1	Nachhaltigkeitszertifikate	CE, Green Premium, RoHS
Notaus-Steckverbinder (EPO)	✓	Gewicht und Abmessungen	
Akku/Batterie		Breite	432 mm
Akku-/Batterietechnologie	Lithium-Ion (Li-Ion)	Tiefe	560 mm
Akku-/Batteriespannung	50 V	Höhe	43 mm
Akkuladezeit	1,5 h	Gewicht	15,9 kg
Hot-Swap-Batterie	✓	Verpackungsbreite	564 mm
Automatischer Batterietest	✓	Verpackungstiefe	764 mm
Kaltstart	✓	Verpackungshöhe	278 mm
Design		Paketgewicht	24,2 kg
Formfaktor *	Rackmount	Verpackungsdaten	
Rack-Kapazität	1U	Mitgelieferte Kabel	RJ-45
Produktfarbe *	Schwarz, Silber		



0731304573616



731304573616

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.